



JEM K1 Hazer

The Jem K1 Hazer is Martin's top-of-the-line hazer for high performance applications where a high level of reliability and easy serviceability is required. Feature-rich and of solid construction, the Jem K1 provides the ideal combination of continuous operation, long hang time, and low fluid consumption for greater economy.

FEATURES

- Designed for service ease
- Continuous output
- Output and density level control
- 5000 m³/min haze output
- Integrated high velocity fan (variable fan speed)
- 600 W heat exchanger
- 2.5 liter fluid capacity
- Low fluid consumption and longer hang-time for greater economy
- Water based - no oil residue on light fixtures
- Automated shut-down procedure to prevent clogging
- On-board DMX, 3 & 5 pin
- On-board control panel
- Fast access set-up mode
- Optional digital remote control
- Silent Mode
- Eco mode extends run time and improves fluid economy

TECHNICAL SPECIFICATIONS

Physical

Length: 544 mm
Width: 459 mm
Height: 344 mm
Dry weight: 21.5 kg

Performance

Coverage volume: 5000 m³ per minute
Max. operating time at full output (approx.): 17 hours
Operating time: Continuous, automatic level adjustment
Warm-up time (approx.): 5 minutes

Control and Programming

Control options: Onboard control panel with 4-digit display
Control options: Instant or timer-controlled output, 0-100% adjustable output level
Control options: Adjustable Fan Speed Level
DMX channels: 2 (output and fan)
Optional digital remote control: 92765036

Construction

Housing: Steel & aluminum
Heat exchanger: 600 W, direct thermal protection

Fluid System

Fluid pump: Oscillating piston, high pressure
Onboard fluid capacity: 2.5 l
Fluid consumption at peak output: 140 ml per hour

Compatible Fluids: Jem K1 Haze Fluid™ only

Installation

Orientation: Floor or flying kit

Connections

Power connection: Neutrik PowerCon
DMX data: 3-pin and 5-pin XLR sockets
Remote control: 3-pin locking XLR

Electrical

AC power (EU models): 220-240 V nominal, 50 Hz
AC power (US models): 110-120 V nominal, 60 Hz
Main fuse (220-240 V power): 5 AT
Main fuse (110-120 V power): 10 AT

Typical Power and Current

US model:

120 V, 60 Hz: 675 W, 6.0 A

EU model:

230 V, 50 Hz: 675 W, 3.1 A

Measurements made at nominal voltage. Allow for a deviation of +/- 10%.

Thermal

Maximum ambient temperature (Ta max.): 40° C
Exterior surface temperature, steady state: 40° C
Max. nozzle temperature: 200° C

Approvals

EU EMC: EN 6100-6-3:2001 - Part 6-3

EU safety: EN 60 335-1:2002

Immunity: EN 61000-6-1:2001 - Part 6-1

ETL approvals (cETLus): UL Std.998, CAN/CSA Std. C22.2 No 104-01

Accessories

K1™ Haze Fluid, 2.5 gal./9.5 ltr.: 97120411

K1™ Haze Fluid, 4 x 2.5 ltr.: 97120407

JEM K1 Hazer Remote Control: 92765036

Ordering Information

Jem K1 Hazer, 110 V: 92225900

Jem K1 Hazer, 240 V: 92225901



A C C E S S O R I E S



Flightcase for 1 x
Jem K1 Hazer
P/N: 91540012



Flying kit, JEM
K1/Hazer Pro
P/N: 92610002



K1 Haze Fluid 2.5
gal./9.5L
P/N: 97120411



K1 Haze Fluid
4x2.5L
P/N: 97120407



Remote Cntrl. K1
Hazer
P/N: 92765036